

Resiste® PDLA

A topcoated, black image product designed for package delivery applications. Resiste® PDLA has medium-high sensitivity and provides suitable environmental resistance and high bar code scan rates.

LABEL FACESTOCK



KEY FEATURES

- Topcoated for handling and storage durability
- Sensitivity for moderate to fast print speeds
- Suitable chemical and environmental resistance
- Moisture resistant

APPLICATIONS

- Package delivery labels
- Warehouse labels
- Industrial labels
- Applications using visible light and/or near infrared scanners

PRODUCT CHARACTERISTICS

Caliper (mils/μm)	3.05 ± 0.15/77.5 ± 4
Basis Weight	
17 x 22—500 (lbs)	18.5 ± 1.0
g/m ²	69.4 ± 3.9
Thermal Response - Nominal	
Static (°C ± 5°)	
0.2 ODU	93
1.0 ODU	110
Maximum Density (ODU)	1.95
Temperature Required	149
Dynamic—Atlantek 400 (mj/mm ²)	
0.2 ODU	5.9
1.0 ODU	8.7
Maximum Density (ODU)	1.85
Energy Required	16.0
Brightness (UV Excluded)	>77
Gurley Stiffness Nominal (mg)	MD 90 CD 45
Elmendorf Tear Nominal (g)	MD 45 CD 46
Tensile (lbs/in)	MD 37 CD 16
Parker Print Surface	<1.70

