

# Résiste<sup>®</sup> 400 - 7.0



An economical standard caliper, standard sensitivity topcoated direct thermal product designed for general-purpose applications. Résiste<sup>®</sup> 400 - 7.0 is backside printable for basic one- or two-color images with excellent lay-flat characteristics.

## ENTERTAINMENT PRODUCTS



## KEY FEATURES

- Topcoated for high resistance
- Unique backside treatment for excellent lay-flat characteristics
- Standard sensitivity delivering 200-dpi images
- Excellent resistance to high heat
- Ideal for one- or two-color backside images
- High caliper for quality feel and stiffness

## APPLICATIONS

- Parking spitter tickets
- Parking receipts
- Cinema tickets
- Bus/rail tickets

## PRODUCT CHARACTERISTICS

<b>Caliper (mils/μm)</b>	7.10 ± 0.30/177.8 ± 8
<b>Basis Weight</b>	
17 x 22—500 (lbs)	44.5 ± 2.2
g/m <sup>2</sup>	167.3 ± 8.4
<b>Thermal Response - Nominal</b>	
Static (°C ± 5°)	
0.2 ODU	87
1.0 ODU	104
Maximum Density (ODU)	1.79
Temperature Required	135
Dynamic—Atlantek 400 (mj/mm <sup>2</sup> )	
0.2 ODU	6.2
1.0 ODU	9.9
Maximum Density (ODU)	1.7
Energy Required	16.0
<b>Brightness (UV Included)</b>	>75
<b>Gurley Stiffness Nominal (mg)</b>	MD 1234 CD 575
<b>Elmendorf Tear Nominal (g)</b>	MD 115 CD 140
<b>Tensile (lbs/in)</b>	MD 73 CD 35
<b>Parker Print Surface</b>	<1.85

