

Résiste[®] 400 - 7.0



An economical standard caliper, standard sensitivity topcoated direct thermal product designed for general-purpose applications. Résiste[®] 400 - 7.0 is backside printable for basic one- or two-color images with excellent lay-flat characteristics.

ENTERTAINMENT PRODUCTS



KEY FEATURES

- Topcoated for high resistance
- Unique backside treatment for excellent lay-flat characteristics
- Standard sensitivity delivering 200-dpi images
- Excellent resistance to high heat
- Ideal for one- or two-color backside images
- High caliper for quality feel and stiffness

APPLICATIONS

- Parking spitter tickets
- Parking receipts
- Cinema tickets
- Bus/rail tickets

PRODUCT CHARACTERISTICS

Caliper (mils/μm)	7.10 ± 0.30/177.8 ± 8
Basis Weight	
17 x 22—500 (lbs)	44.2 ± 3.5
g/m ²	166 ± 13.3
Thermal Response - Nominal	
Static (°C ± 5°)	
0.2 ODU	87
1.0 ODU	104
Maximum Density (ODU)	1.79
Temperature Required	135
Dynamic—Atlantek 400 (mj/mm ²)	
0.2 ODU	6.2
1.0 ODU	9.9
Maximum Density (ODU)	1.7
Energy Required	16.0
Brightness (UV Included)	>75
Gurley Stiffness Nominal (mg)	MD 1234 CD 575
Elmendorf Tear Nominal (g)	MD 115 CD 140
Tensile (lbs/in)	MD 73 CD 35
Parker Print Surface	<1.85

